

ICafe Menu Download

Install Package Manual

Port Forward in Mikrotik Router

Down and dirty version. The command line version is below the Winbox instructions. Let's say you have a DVR that has a static IP of 192 port 3999.

In Winbox

1) Go to IP -> Firewall -> NAT (Figure 1-1).



Figure 1-1

2) Click the "+" to add a new NAT rule. Modify the "Chain" to "dstnat", "Protocol" to "tcp", and "Dst. Port" to "3999". Set the "In. Interface telling the router that any traffic coming IN from the Internet on port 3999 should follow this rule. If you forget this step, the router will

Safe Mode		mbox v3.13 on Kb7300c (mipsbe)	
	Firewall	New NAT Rule	
Bridge	Filter Rules NA	General Advanced Extra Action Statistics	
PPP		Christ Land	
Switch	# Action		
Mesh	;;; default confi	Src. Address:	
IP D	0 ≓ll mas	Dst. Address:	
MPLS N		Protocol: 6 top)	ī
Routing 1			
System 🗅		Src. Port:	
Queues		Dst. Port: 3999	
Files		Any. Port:	
Log		In. Interface: 🔲 ether1-gateway	Ŧ
Radius		Out. Interface:	
Tools N		-	
New Terminal		Packet Mark:	
MetaROUTER		Connection Mark:	
Make Supout.rif		Routing Mark:	
Manual		Bouting Table:	
Exit			
×		Connection Type:	
Bo			
Vin			
>			
ö			
Ē			
no	•		
∝	1 item		

Figure 1-2

3) Click the "Action" tab, change the "Action" value to "dst-nat", the "To Addresses" to "192.168.1.200" and "To Ports" to "3999" (

Interfaces	Firewall	NAT Rule <3999>
Bridge	Filter Rules NA	General Advanced Extra Action Statistics
PPP	+	Action: dst-nat
Switch	# Action	To Addresses: 192.168.1.200
Mesh	;;; default confi	T D 2000
IP N	1 √acc	To Ports: 3999
MPLS N		
Routing N		
System 🗅		
Queues		
Files		
Log		
Radius		
Tools 🗅		
New Terminal		
MetaROUTER		
Make Supout.rif		
Manual		
Exit		

Figure 1-3

Terminal Version

Type the following value into a Terminal window to enter this port forwarding rule.

/ip firewall nat

add action=dst-nat chain=dstnat disabled=no dst-port=3999 in-interface=ether1-gateway protocol=tcp to-addresses=192.168.1.

Copyright(C) 2000-2020 Youngzsoft Inc. All Rights Reserved. Privacy policy